

ROLLING MILL TRAIN Mod. "TMP6T E"- "TMP6T S"- "TMP6T IBH"



TECHNICAL CARD:

ROLLER DIAMETER	93 mm
ROLLER WIDTH	85 mm
VARIABLE SPEED	0-80 m/min
HEADS	6
TOTAL STEPS	30
HEAD MOTOR	2,2 KW
COILER MOTOR	1,5 KW
WIRE REDUCTION	FROM Ø8 TO 1x1 mm
ROLLS SUPPORT	ROLLER BEARING
LUBRICATION SYSTEM TROUGH MOTORIZED PUMP ON WIRE	
DIMENSIONS	3.000x1.000x1.700 H (mm)
WEIGHT	3.400 Kg



OTHER CHARACTERISTICS Mod. "TMP6T E"

EXIT SIZE 1	FROM Ø8 TO 4,9mm
EXIT SIZE 2	FROM 4,9 TO 3,3mm
EXIT SIZE 3	FROM 3,3 TO 2,3mm
EXIT SIZE 4	FROM 2,3 TO 1,6mm
EXIT SIZE 5	FROM 1,6 TO 1 mm
ALIGNMENT MOTOR (BRUSHLESS)	2 MOTORS
HEAD MOTOR SPEED SETTINGS	NO
HEAD MOTOR TORQUE SETTINGS	NO
SOFTWARE FOR MACHINE CONTROL	NO
DISPLAY TOUCH SCREEN	NO

OTHER CHARACTERISTICS Mod. "TMP6T S"

EXIT SIZE 1	FROM Ø8 TO 4,9mm
EXIT SIZE 2	FROM 4,9 TO 3,3mm
EXIT SIZE 3	FROM 3,3 TO 2,3mm
EXIT SIZE 4	FROM 2,3 TO 1,6mm
EXIT SIZE 5	FROM 1,6 TO 1 mm
ALIGNMENT MOTOR (BRUSHLESS)	2 MOTORS
HEAD MOTOR SPEED SETTINGS	YES
HEAD MOTOR TORQUE SETTINGS	YES
SOFTWARE FOR MACHINE CONTROL	YES
DISPLAY TOUCH SCREEN	YES

OTHER CHARACTERISTICS Mod. "TMP6T IBH"

30 EXIT SIZE IN ACCORDING WITH REDUCTION LIST FROM 6,7 mm TO 1x1 mm

ALIGNMENT MOTOR (BRUSHLESS)	6 MOTORS
HEAD MOTOR SPEED SETTINGS	YES
HEAD MOTOR TORQUE SETTINGS	YES
SOFTWARE FOR MACHINE CONTROL	YES
DISPLAY TOUCH SCREEN	YES